



Quality System Certified to ISO 9001:2008

SAI Global File #004008

Burlington, Ontario, Canada

SUPER COLD 134

403A-AEROSOL

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: Super Cold 134

SDS Code: 403A-Aerosol

Related Part # 403AR-285G, 403A-450G

Recommended Use and Restriction on Use

Use: For cooling electronic components and locating thermal intermittents

Uses Advised Against: Not available

Details of Manufacturer or Importer

Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

MG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA

☎ +1-800-340-0772
FAX +1-800-340-0773
E-MAIL support@mgchemicals.com
WEB www.mgchemicals.com

☎ +1-905-331-1396
FAX +1-905-331-2682
E-MAIL info@mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY—leaks, spills, fires, exposures or accidents
USA or CANADA: Call CHEMTREC ☎: **+1-800-424-9300**


For emergencies involving dangerous goods; Collect 24/7
CANADA: Call CANUTEC ☎: **+1-613-996-6666** or ***666** on cellular phones

SUPER COLD 134**403A-AEROSOL****Section 2: Hazard(s) Identification****Classification of Hazardous Chemical****GHS Categories**

Criteria	Category	Signal Word	Pictograms
Gas Under Pressure Liquefied Gas	Liquefied Gas	Warning	Gas Cylinder

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	WARNING
Pictograms	Hazard Statements
	H280: Contains gas under pressure; may burst if heated
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.
P251	Do not pierce or burn, even after use.
Storage	Precautionary Statements
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].

Section continued on the next page

SUPER COLD 134
403A-AEROSOL
Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Simple Asphyxiants	May displace oxygen and cause rapid suffocation.	Warning	<i>none</i>
Frostbite	The jet or liquid may cause frostbite in contact with skin or eyes.	Warning	<i>none</i>
Inhalation overexposure	Inhalation overexposure following an intentional abuse or use in confined space may cause cardiac or central nervous systems effects.	<i>none</i>	<i>none</i>

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
811-97-2	1,1,1,2-tetrafluoroethane ^{a)}	100%

a) Also known as HFC 134a

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF INHALED	P304 + P340, P312
Immediate Symptoms	<i>dizziness, drowsiness, heart thumping</i>
Response	Remove person to fresh air and keep comfortable for breathing. If you feel unwell: Call a POISON CENTRE/doctor.
IF IN EYES	P305 + P351 + P338, P336 + P315
Immediate Symptoms	<i>frostbite, cold burns</i>
Response	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If frostbite occurs: Thaw frosted parts with lukewarm water. Do not use hot water. Do not rub affected area. Get immediate medical attention.

Section continued on the next page

SUPER COLD 134**403A-AEROSOL**

IF ON SKIN	P302 + P352, P336 + P315
Immediate Symptoms	<i>frostbite, cold burns</i>
Response	IF ON SKIN: Wash with plenty of water. If frostbite occurs: Thaw frosted parts with lukewarm water. Do not use hot water. Do not rub affected area. Get immediate medical attention.
IF SWALLOWED	P301 + P330, P314
Immediate Symptoms	<i>frostbite (mouth)</i>
Response	IF SWALLOWED: Rinse mouth. IF feeling unwell: Get medical advice/attention.

Medical Advice

Avoid giving catecholamine drugs (such as epinephrine) due to possible cardiac disturbance. Treat symptomatically.

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish. Use water spray to cool containers.
Specific Hazards	Aerosols containers may erupt with force at temperatures above 50 °C [122 °F]. Produces irritating and toxic fumes in fires or in contact with hot surfaces. The vapors are heavier than air and may displace oxygen in low-lying areas creating a suffocation hazard.
Combustion Products	Produces carbon oxides (CO,CO ₂), halogenated compounds, and hydrogen fluorides.
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

SUPER COLD 134**403A-AEROSOL****Section 6: Accidental Release Measures**

Personal Protection	See personal protection recommendations in Section 8. For very large spills, wear self-contained breathing apparatus before approaching the spill. Wear cold-insulating clothing and gloves.
Precautions for Response	For aerosol can spills in confined or low lying space, leave the immediate spill area. If it can safely be done, extinguish open flames or remove high temperature sources to avoid producing toxic decomposition products.
Environmental Precautions	Not required under normal use.
Containment Methods	Not applicable
Cleaning Methods	For aerosol can spills at room temperature, the product turn gaseous and disperse in atmosphere. Ensure adequate ventilation, especially in low or enclosed areas.
Disposal Methods	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention	Keep out of reach of children. Avoid direct skin or eye contact with liquid or aerosol jet. Avoid breathing gas/spray. In cases of inadequate ventilation wear respiratory protection. Do not pierce or burn, even after use.
Handling	Wear cold-insulating gloves if exposure to liquid or aerosol jet is likely. Wear eye protection.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].

SUPER COLD 134**403A-AEROSOL****Section 8: Exposure Controls/Personal Protection****Substances with Occupational Exposure Limit Values**

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
1,1,1,2- tetrafluoroethane	MG Chemicals ^{a)} ACGIH U.S.A. OSHA PEL Canada	1 000 ppm Not established Not established Not established	Not established Not established Not established Not established

Note: The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS database² and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) MG Chemicals recommended limit corresponding to prevalent international threshold values

Engineering Controls**Ventilation**

Keep airborne concentrations below the occupational exposure limits (OEL).

General ventilation is adequate for normal use; keep overall exposure as low as possible.

Personal Protective Equipment**Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

Recommendation: Ensure that glasses have side shields for lateral protection.

Skin Protection

If exposure to the jet or liquid is likely, wear cold-insulating gloves to protect the skin against frostbites.

Respiratory Protection

For extreme exposures, use self-contained breathing apparatus or supplied by air.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

SUPER COLD 134**403A-AEROSOL****Section 9: Physical and Chemical Properties**

Physical State	Liquified gas, in aerosol format	Lower Flammability Limit	Not applicable
Appearance	Colorless	Upper Flammability Limit	Not applicable
Odor	Slight, ether-like	Vapor Pressure @25 °C	630 kPa [4 725 mmHg]
Odor Threshold	Not available	Vapor Density	3.5 (Air =1)
pH	Not Available	Specific Gravity @25 °C	1.21
Freezing/Melting Point	-101 °C [-150 °F]	Solubility in Water	0.15% (wt)
Boiling Point ^{a)}	-26.2°C [-15.2 °F]	Partition Coefficient	1.06 ^{a)}
Flash Point	None detected	Auto-ignition Temperature	750 °C [1 382 °F]
Evaporation Rate	≥1 (Ether = 1)	Decomposition Temperature	Not available
Flammability (solid, gas)	Not available	Viscosity @40 °C	Not available

Note: Literature values are used.

a) Octanol-water LogP value

Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures.
Conditions to Avoid	Temperatures above 50 °C [122 °F], open flames, and incompatible substances
Incompatibilities	Strong oxidizing agents, alkali or alkali earth metals, powdered aluminum, zinc, magnesium, and beryllium
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

SUPER COLD 134**403A-AEROSOL****Section 11: Toxicological Information****Routes of Exposure**

Eye contact, Ingestion, Inhalation, and Skin contact

Symptoms Summary

Eyes	See skin symptoms.
Skin	Contact with the liquid may cause frostbite due to heat lost caused by rapid evaporation. Exposure to the jet can also lead to frostbites, because it can reach -55 °C [-67 °F].
Inhalation	Extreme exposure may cause central nervous system depression and irregular heart beat.
Ingestion	See inhalation and skin symptoms.
Chronic	No chronic effects known.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
1,1,1,2-tetrafluoroethane	Not available	Not available	1 500 g/m ³ 4 h Rat

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier (M)SDS were also consulted.

Other Toxicological Effects

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/irritation	Based on available data, the classification criteria are not met.
Sensitization (allergic reactions)	Based on available data, the classification criteria are not met.
Carcinogenicity (risk of cancer)	Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met. No mutagenic effects observed in four tests.

Section continued on the next page

SUPER COLD 134**403A-AEROSOL****Reproductive Toxicity**

(risk to sex functions)

Based on available data, the classification criteria are not met.

Teratogenicity

(risk of fetus malformation)

Based on available data, the classification criteria are not met. No observed effect level (NOEL) for rabbit and rat is 40 000 ppm.

STOT-single exposure

Based on available data, the classification criteria are not met. Can affect the central nervous system and cardiovascular systems by inhalation at extreme doses that do not give rise to classification.

STOT-repeated exposure

Based on available data, the classification criteria are not met. The chronic no observed effect level is 10 000 ppm.

Aspiration hazard

Based on available data, the classification criteria are not met.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The 1,1,1,2-tetrafluoroethane substance is not classifiable as an environmental toxicant.

Acute Ecotoxicity

Based on available data, the classification criteria are not met.

Chronic Ecotoxicity

Based on available data, the classification criteria are not met.

Biodegradability

No data available

Other Effects**Global Warming Potential**

The 100 years global warming potential is 1430.

VOC (Volatile Organic Compounds) exempted substance according to the US (EPA) and Canadian (CEPA) authorities.

SUPER COLD 134**403A-AEROSOL****Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information**Ground****Refer to USA DOT 49 CFR (Parts 100 to 185) Regulations.****Limited Quantity****USA**

UN number: Not applicable
Shipping Name: Not applicable
Class: Not applicable
Packing Group: Not applicable
Marine Pollutant: No

USA—Special Provision: Refer to DOT-SP 10232. A copy of this special permit is required. <http://www.sextoncan.com/pdf/certification/DOT-SP10232.pdf>

Refer to TDG(Canadian Transportation of Dangerous Goods regulations) Regulations.**Limited Quantity****Canada and Global (Excluding USA)**

UN number: Not applicable
Shipping Name: Not applicable
Class: Not applicable
Packing Group: Not applicable
Marine Pollutant: No

CANADA—Permit for Equivalent Level of Safety: Refer to TC-SU 11282.
<http://wwwapps.tc.gc.ca/wwwdocs/TDGCertificates/doc/11282-eng.doc>

Section continued on the next page

SUPER COLD 134**403A-AEROSOL****Air****Refer to ICAO-IATA Dangerous Goods Regulations.****Limited Quantity**

USA

UN number: UN3159**Shipping Name:** 1,1,1,2-Tetrafluoroethane**Class:** 2.2**Packing Group:** Not applicable**Marine Pollutant:** No**USA—Special Provision:** Refer to DOT-SP 10232. A copy of this special permit is required. <http://www.sextoncan.com/pdf/certification/DOT-SP10232.pdf>*Note:* Avoid shipping by air if possible.**Refer to ICAO-IATA Dangerous Goods Regulations.****Limited Quantity**

Canada and Global (Excluding USA)

UN number: UN1950**Shipping Name:** AEROSOL, non-flammable**Class:** 2.2**Packing Group:** Not applicable**Marine Pollutant:** No**CANADA—Permit for Equivalent Level of Safety:** Refer to TC-SU 11282. <http://wwwapps.tc.gc.ca/wwwdocs/TDGCertificates/doc/11282-eng.doc>*Note:* Avoid shipping by air if possible.**Sea****Refer to IMDG Regulations.****Limited Quantity**

USA


UN number: UN3159**Shipping Name:** 1,1,1,2-Tetrafluoroethane**Class:** 2.2**Packing Group:** Not applicable**Marine Pollutant:** No**USA—Special Provision:** Refer to DOT-SP 10232. A copy of this special permit is required. <http://www.sextoncan.com/pdf/certification/DOT-SP10232.pdf>*Section continued on the next page*

SUPER COLD 134**403A-AEROSOL****Refer to IMDG Regulations.****Limited Quantity**

Canada and Global (Excluding USA)

UN number: UN1950**Shipping Name:** AEROSOL, non-flammable**Class:** 2.2**Packing Group:** Not applicable**Marine Pollutant:** No**CANADA—Permit for Equivalent Level of Safety:** Refer to TC-SU 11282.<http://wwwapps.tc.gc.ca/wwwdocs/TDGCertificates/doc/11282-eng.doc>

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information**Canada****WHMIS 1988 Classification**

A – Aerosol Container

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.


Health Canada

Products produced by MG Chemicals intended for retail display conform to the Canadian Consumer Labeling Regulations.

Section continued on the next page

SUPER COLD 134**403A-AEROSOL****USA****Other Classifications****HMIS[®] RATING**

HEALTH:	* 1
FLAMMABILITY:	0
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA[®] 704 CODES

Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substances which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, June 06, 2014 revision, USA).

This product does not contain any of the listed substances.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

SUPER COLD 134**403A-AEROSOL****Section 16: Other Information****SDS Prepared by** Michel Hachey**Date of Revision** 26 February 2016**Supersedes** 24 November 2015**Reason for Changes:** Product name error correction in Section 1.**Reference**

1) ACGIH 2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Section continued on the next page



Quality System Certified to ISO 9001:2008

SAI Global File #004008

Burlington, Ontario, Canada

SUPER COLD 134

403A-AEROSOL

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.