



SPINKS ACRYLIC, ALL CODES

MSDS Number

CCTQH

National Stock Number

7510-00N075217

Product Name

SPINKS ACRYLIC, ALL CODES

Manufacturer

SPINKS DRYCO INC

Product Identification

Product ID:SPINKS ACRYLIC, ALL CODES

MSDS Date:09/01/1993

FSC:7510

NIIN:00N075217

MSDS Number: CCTQH

Responsible Party

SPINKS DRYCO INC

961 APRICOT AVE

SARASOTA , FL 34337

US

Emergency Phone: 813-366-3336

Info Phone: 813-366-3336

Cage: SPXNK

Contractor

SPINKS DRYCO INC

SARASOTA, FL 34337

US

813-366-3336

Cage: SPXNK

Ingredients

NON-HAZARDOUS INGREDIENTS

OSHA PELN/K

ACGIH TLV: N/K

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:BECAUSE OF THE DEFATTING PROPERTY IN CERTAIN INGREDIENTS, SKIN CONTACT MAY RESULT IN DRYNESS AND/OR IRRITATION AND DERMATITIS MAY DEVELOP WITH PROLONGED EXPOSURE. EYE IRRITATION IS ALSO POSSIBLE.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:IT IS EXPECTED THAT SKIN CONTACT MAY AGGRAVATE AN EXISTING DERMATITIS.

First Aid

First Aid:INHALATION:REMOVE FROM EXPOSURE, RESTORE BREATHING. CALL



PHYSICIAN. EYES:FLUSH WITH WATER FOR AT LEAST 15 MINUTES. CALL
PHYSICIAN. SKIN:WASH WITH SOAP AND WATER, REMOVE CONTAMINATED
CLOTHING. INGESTION:DO NOT INDUCE VOMITING.

Fire Fighting

Flash Point Method:SCC
Flash Point:>200F,>93C
Extinguishing Media:USE WATER FOG, FOAM, CO₂ OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR NIOSH APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT . WATER SPRAY MAY BE USED TO COOL CLSD CNTNRS TO PVNT
PRESS BUILD-UP & POSS AUTO-IGNIT WHEN (SUPDAT)
Unusual Fire/Explosion Hazard:DENSE SMOKE MAY BE GENERATED WHEN
BURNING.

Accidental Release

Spill Release Procedures:WIPE UP-DISPOSE OF WIPERS IN CONTAINERS
APPROVED FOR OILY WASTES.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE IN SEALED CONTAINERS AWAY FROM
HEAT, OPEN FLAMES AND OXIDIZING MATERIALS. FIRE EXTING READILY
AVAILABLE AND PERS TRAINED IN ITS PROPER USE.
Other Precautions:FOR INDUSTRIAL USE ONLY. DO NOT TAKE INTERNALLY. DO
NOT REUSE CONTAINER FOR OTHER PURPOSES.

Exposure Controls

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR APPROPRIATE FOR
EXPOSURE OF CONCERN . NONE REQUIRED IN NORMAL USAGE.
Ventilation:GENERAL VENTILATION OR LOCAL EXHAUST VENTILATION OR AS
SPECIFIED BY LOCAL OR STATE REQUIREMENTS.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:ANSI APPROVED CHEM WORKERS GOGGLES .
Other Protective Equipment:ANSI APPROVED EMERGENCY EYE WASH AND DELUGE
SHOWER . NONE.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
% VOLAT (EPA METHOD 24):20 (WT). FIRE FIGHT PROC:EXPOSED TO EXTREME
HEAT. WHEN WATER IS USED, FOG NOZZLES ARE PREFERABLE.

Chemical Properties

Boiling Pt:B.P. Text:>520F,>271C
Vapor Density:HVR/AIR
Evaporation Rate & Reference:SLOWER THAN BUTYL ACETATE
Solubility in Water:NONE
Appearance and Odor:COLORED PASTE; OILY ODOR.
Percent Volatiles by Volume:SUPDAT

Stability

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.
Stability Condition to Avoid:HEAT, SPARKS AND OPEN FLAME.
Hazardous Decomposition Products:CO AND CO₂ ON BURNING.

Disposal

Waste Disposal Methods:IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.