Material Safety Data Shee May be used to comply with	et	U.S. Department of Labor	H
OSHA's Hazard Communication St.	landard.	Occupational Safety and Health Administration (Non-Mandatory Form)	
29 CFR 1910.1200. Standard must consulted for specific requirements.	t he	Form Approved	F
		OMB No. 1218-0072	HAMMABILU
IDENTITY (As Used on Label and List)	BARBICIDE	Note. Blank spaces are not permitted. If any item is no information is available, the space must be market	ed to in REACTIVITY
Section i			PERSONAL
Manufacturer's Name KING RESEARCH, INC.		Emergency Telephone Number	PROTECTION
Address (Number, Street, City, State, and	ad ZIP Code	(718) 788-0122 Telephone Number for Information	<u> </u>
114 - 12th STREET	io zii obucj	(718) 788-0122	
BROOKLYN, NY 11215		Date Prepared	
		MAY 1, 2002 Signature of Preparer (optional)	
Section II — Hazardous Ingred	dients/Identity Information		
Hazardous Components (Specific Chem	nical Identity; Common Name(s))	Other Limits OSHA PEL ACGIH TLV Recommende	ed % (options
ISOPROPYL ALCOHOL		CAS #000067-63-0	13%
DIMETHYL BENZYL AMMO	NIUM CHLORIDE	CAS #68424-85-1	5.127
SODIUM NITRITE		CAS #7632-00-0	2%
Section III — Physical/Chamles			
	at Characteristics	Specific Granty /H-O = 1	
loiling Point	of Characteristics	Specific Gravity (H _Z O = 1)	1.00
oiling Point	212° F	Specific Gravity (H ₂ O = 1) Melting Point	
oiling Point apor Pressure (mm Hg.)	212° F N/A	Melting Point Evaporation Rate	N/A
Point Pressure (mm Hg.) Paper Density (AIR = 1) Polubility in Water	212° F N/A N/A	Melting Point	
	212° F N/A	Melting Point Evaporation Rate	N/A
oiling Point apor Pressure (mm Hg.) apor Density (AIR = 1) olubility in Water COMPLETE poppearance and Odor	212° F N/A N/A	Melting Point Evaporation Rate	N/A
apor Pressure (mm Hg.) apor Density (AIR = 1) olubility in Water COMPLETE pi ppearance and Odor BLUE LIQUID	212° F N/A N/A H 9.0 - 10.1 WITH PLEASANT ODOR	Melting Point Evaporation Rate	N/A
oiling Point apor Pressure (mm Hg.) apor Density (AIR = 1) olubility in Water COMPLETE poppearance and Odor BLUE LIQUID to the control of the control o	212° F N/A N/A H 9.0 - 10.1 WITH PLEASANT ODOR	Melting Point Evaporation Rate (Butyl Acetate = 1) Flammable Limits LEL	N/A
oiling Point apor Pressure (mm Hg.) apor Density (AIR = 1) olubility in Water COMPLETE p pepearance and Odor BLUE LIQUID ection IV — Fire and Explosio ash Point (Method Used) 91° F thinguishing Media	212° F N/A N/A H 9.0 - 10.1 WITH PLEASANT ODOR On Hazard Data (Tag Closed Cup)	Melting Point Evaporation Rate (Butyl Acetare = 1) Flammable Limits N/A	N/A N/A
apor Pressure (mm Hg.) apor Density (AIR = 1) clubility in Water COMPLETE pi ppearance and Odor BLUE LIQUID 1 ection IV — Fire and Explosion ash Point (Method Used) 91° F stinguishing Media Water, dry	212° F N/A N/A H 9.0 - 10.1 WITH PLEASANT ODOR on Hazard Data	Melting Point Evaporation Rate (Butyl Acetare = 1) Flammable Limits N/A	N/A N/A
oiling Point apor Pressure (mm Hg.) apor Density (AIR = 1) blubility in Water COMPLETE pi ppearance and Odor BLUE LIQUID 1 ection IV — Fire and Explosio ash Point (Method Used) 91° F tinguishing Media Water, dry (212° F N/A N/A H 9.0 - 10.1 WITH PLEASANT ODOR ON Hazard Data (Tag Closed Cup) chemical, carbon di	Melting Point Evaporation Rate (Butyl Acetare = 1) Flammable Limits N/A	N/A N/A
apor Pressure (mm Hg.) apor Density (AIR = 1) olubility in Water COMPLETE pi ppearance and Odor BLUE LIQUID 1 ection (V — Fire and Explosio ash Point (Method Used) 91° F stinguishing Media Water, dry opecial Fire Fighting Procedures	212° F N/A N/A H 9.0 - 10.1 WITH PLEASANT ODOR ON Hazard Data (Tag Closed Cup) chemical, carbon di	Melting Point Evaporation Rate (Butyl Acetare = 1) Flammable Limits N/A	N/A N/A

Section V -	- Reactivity Data	3					
Stability	Unstable	7	Conditions to Avoid				
	Stable	+		·			
Incompatibility	(Materials to Avoid)	<u> </u>	<u></u>				
Hazardous Deci	omposition or Byprodi	ucts					
Hazardous		1			· · · · · · · · · · · · · · · · · · ·		
Polymerization	May Occur Will Not Occur	ļ	Conditions to Avoid	<u> </u>			
		X					
	- Health Hazard						
Route(s) of Entr		lation?		Skin? X		Ingestion? X	
Health Hazards	(Acute and Chronic)	EYE:	Direct contact m	ау са	use eye dam		
		SKIN:	Repeated contact	can	cause irrit	ation	
			-				
Carcinogenicity:	NTP 1	? 10		IARC Mo	nographs? NO	OSHA Regulated?	
					·		
Signs and Symp	oloms of Exposure	4i1d	irritation of muc	ous m	embrane		
							<u> </u>
Medical Condition Generally Aggra-	ns vated by Exposure	N/	A				
F							
emergency and	First Aid Procedures	Skin	and Eye Contact:	Flus	h with water	r for 15 minutes. C	all
	a physician.					er, call a physician	
Section VII -	 Precautions for 	r Safe	Handling and Use	11115, 216			
Steps to Be Take	en in Case Material Is	Releas	ed or Spilled with water.				
7		THOIL	WICH WOLEI.				
							·
Waste Disposal I	Method)	se of on site				
						aste disposal facili	ty.
Precautions to Br	Taken in Handling	rap and Stor	container and put	in t	rash.		
			Store in cool a	rea a	t room tempe	erature. Avoid freez	ing.
Other Precautions							
	· · · · · · · · · · · · · · · · · · ·				····		
				<u>.</u>			
	- Control Measu	ires					
tespiratory Protei	ction (Specify Type) N	l0ne	required for norm	al ope	erations.		
/entitation	Local Exhaust				Special		
	Mochanical (General)		X		Other		
rotective Gloves	Rubber or Ne			Eye Pr	otection		
Other Protective C	Clothing or Equipment			<u> </u>		Proof Goggles	
Vork/Hygienic Pra	actices		ervious Apron - E				
		Hand	lle this and all o	hemio	als with ca	re.	