Product Name: Multi-Purpose Epoxy Cartridge

Product identifier: 100818 Revision Date: 07-18-2015

Replaces:



1. Identification

Product Name: Multi-Purpose Epoxy Cartridge

Product identifier: 100818

Relevant identified uses of the

substance or mixture and uses

advised against:

Epoxy Adhesive

Chemical Manufacturer / ITW Evercoat

Importer / Distributor: a division of Illinois Tool Works Inc.

6600 Cornell Road Cincinnati, OH 45242

513-489-7600

Emergency telephone number: CHEMTREC: 1-800-424-9300

CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols:



GHS Classification: Carcinogenicity Category 1A

Reproductive Toxicity Category 1B

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1 Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1

Germ Cell Mutagenicity Category 2

Hazardous to the aquatic environment - Acute Category 3

Flammable Liquid Category 4

GHS Signal Word: Danger

GHS Hazard Statements: Cumbustible Liquid

Suspected of causing genetic defects.

May cause cancer.

May damage fertility or the unborn child.

Causes damage to organs.

Causes damage to organs through prolonged or repeated exposure.

Harmful to aquatic life.

Product Name: Multi-Purpose Epoxy Cartridge

Product identifier: 100818 Revision Date: 07-18-2015

Replaces:

GHS Precautionary Statements:

Safety Precautions: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

First Aid Measures: IF exposed: Call a POISON CENTER or doctor/physician.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label). In case of fire: Use for extinction.

Storage: Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal: Dispose of contents/container in accordance with

local/regional/national/international regulation for hazardous wastes.

Hazards not otherwise

classified:

No data available

3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient	
Styrene	100-42-5	1 - 5	
2,4,6-Tris[(Dimethylamino) Methyl]	90-72-2	0.5 - 1.5	
Phenol			
Crystalline Silica (Quartz)	14808-60-7	0.1 - 1	

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Eye Contact: Flush eyes with plenty of water for at least 20 minutes retracting

eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention. Flush eyes gently with water for at least 15 minutes, lifting upper & lower

eye lids. Seek immediate medical attention.

Skin Contact: Wash with soap and water. Get medical attention if irritation

develops or persists. Remove contaminated clothing and continue

Product Name: Multi-Purpose Epoxy Cartridge

Product identifier: 100818 Revision Date: 07-18-2015

Replaces:

flushing with water. Wash affected area thoroughly with soap and

water. Seek medical advice if symptoms persist

Inhalation: Remove to fresh air. If breathing is difficult, have a trained

individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately Remove person to fresh air. Seek immediate medical attention. If the victim has stopped breathing open airway, loosen collar and belt, and administer artificial

respiration.

Ingestion: Do not induce vomiting and seek medical attention immediately.

Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. Call a physician or poison control center immediately. Do not induce vomiting unless directed to do so by

medical personnel.

Most important Prolonged or repeated exposure may cause asthma and skin

symptoms/effects (Delayed: Immediate medical attention and special treatment needed,:

Special protective equipment

and precautions for fire-

sensitization or other allergic response.

No additional first aid information available

5. Fire-fighting measures

Products:

fighters:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water

spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire. Do not direct a water stream directly into the hot burning liquid. Regular foam Carbon dioxide Dry

chemical

Unsuitable extinguishing media: No data available

Fire and/or Explosion Hazards: Material may be ignited if preheated to temperatures above the

flash point in the presence of a source of ignition.

Hazardous Combustion Carbon dioxide, Carbon monoxide, Ammonia, Nitrogen containing

gases, oxide gas, Phenolic compounds, Hydrogen sulfide

Do not enter fire area without proper protection including selfcontained breathing apparatus and full protective equipment. Fight

fire from a safe distance and a protected location due to the

potential of hazardous vapors and decomposition products. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme

heat.

Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal

protective equipment.

Product Name: Multi-Purpose Epoxy Cartridge

Product identifier: 100818 Revision Date: 07-18-2015

Replaces:

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Methods and material for containment and cleaning up: No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment

recommendations found in Section VIII of this MSDS

No special spill clean-up considerations. Collect and discard in regular trash. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. All personnel in the area should be protected as in Section 8. Avoid breathing vapors. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

7. Handling and storage

Precautions for safe handling: Mildly irritating material. Avoid unnecessary exposure. All hazard

precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take

internally. Keep out of the reach of children.

Conditions for safe storage: Store in a cool dry place. Isolate from incompatible materials. Store

in a cool dry place Keep away from heat, sparks, and flame Avoid

contact with incompatible materials.

Materials to Avoid/Chemical

Incompatibility::

Oxidizing materials Acids Caustics (bases)

8. Exposure controls/personal protection

Limits:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL		
Styrene	100 ppm	20 ppm	40 ppm STEL; 170 mg/m3		
			STEL		

Appropriate engineering

controls.:

No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits. Explosion proof exhaust ventilation should be used.

Eye Protection:

Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses. Splash proof chemical goggles are recommended to protect against the splash of product.

Product Name: Multi-Purpose Epoxy Cartridge

Product identifier: 100818 Revision Date: 07-18-2015

Replaces:

Skin Protection: Not normally considered a skin hazard. Where use can result in skin

contact, practice good personal hygiene and wear a barrier cream and/or impervious surgical style gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Protective gloves and proper clothing

should be worn to prevent skin contact.

Respiratory Protection: Respiratory protection may be required to avoid overexposure

when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Use

a NIOSH approved respirator designed to remove particulate

matter and organic solvent vapors.

Other Protective Equipment: Splash proof chemical goggles are recommended to protect against

the splash of product. Protective gloves and proper clothing should

be worn to prevent skin contact.

General Hygiene Conditions: All hazard precautions given in the data sheet must be observed.

Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not

take internally. Keep out of the reach of children.

9. Physical and chemical properties

Appearance (physical state):

Color:

Black
Odor:

Amine

Odor threshold:

pH:

No data available

No data available

Melting Point/Freezing Point (°C):

No data available

Initial Boiling Point and Boiling Range (°C): 825 Flash Point (°C): 63

Evaporation Rate:

Flammability (solid, gas):

Upper Flammable/Explosive Limit:

Lower Flammable/Explosive Limit:

No data available

No data available

Vapor Pressure:

No data available

Vapor Density: Heavier than air. Vapors that evolve from this product

will tend to settle and accumulate near the floor.

Relative Density: Not determined

Solubility(ies): Insoluble Partition coefficient: n-octanol/water: 1.36
Auto-ignition Temperature (°C): 490 °C

Decomposition Temperature::No data available
Viscosity:
No data available

Product Name: Multi-Purpose Epoxy Cartridge

Product identifier: 100818 Revision Date: 07-18-2015

Replaces:

10. Stability and reactivity

Reactivity: No data available

Chemical stability: Stable under normal conditions. **Conditions to avoid:** None known. Contamination.

Incompatible materials: Oxidizing materials Acids Caustics (bases)

Hazardous decompositionCarbon dioxide Carbon monoxide Ammonia oxides of nitrogen

products: Phenolic compounds Hydrogen sulfide

11. Toxicological information

Likely routes of exposure (inhalation, ingestion, skin and

eye contact):

Ingestion, Skin contact, Eye contact, Absorption, , Inhalation, ,

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation: Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and

headache. Excessive inhalation of vapors may cause nasal and respiratory irritation,

acute nervous system depression, fatigue, weakness, nausea, headache and

dizziness.

Skin Contact: Can cause minor skin irritation, defatting, and dermatitis.

Skin Absorption: No absorption hazard in normal industrial use. Contact may cause irritation and

possible dermatitis or sensitization.

Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently

injure eye tissue. Contact with liquid or vapor may result in irritation, redness,

tearing, and blurred vision.

Ingestion Irritation: Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea. Causes gastrointestinal tract irritation, nausea, vomiting, diarrhea and possible ulcerations to mucous membranes. Aspiration of material into

the lungs can cause chemical pneumonitis which can be fatal.

Ingestion Toxicity: Harmful if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects:

Carcinogenicity: May cause cancer. The International Agency for Research on Cancer (IARC) has

classified styrene as a group 2B carcinogen (possibly carcinogenic to humans).

Reproductive and

May damage fertility or the unborn child.

Developmental Toxicity:

Mutagenicity: Suspected of causing genetic defects.

Inhalation: Upon prolonged and/or repeated exposure, can cause moderate respiratory

irritation, dizziness, weakness, fatique, nausea and headache.

Skin Contact: Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and

dermatitis.

Skin Absorption: Upon prolonged or repeated exposure, no hazard in normal industrial use.

Product Name: Multi-Purpose Epoxy Cartridge

Product identifier: 100818 **Revision Date: 07-18-2015**

Replaces:

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50	
No data available				

Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
Styrene	N	Υ	Υ
Crystalline Silica (Quartz)	Υ	Υ	Υ

12. Ecological information

Ecotoxicity (aquatic and Toxic to aquatic life. This material is toxic to aquatic organisms and terrestrial, where available):

should not be released to sewage, draining systems or any body of water exceeding concentrations of approved limits under applicable

regulations and permits.

Persistence and degradability:

Mobility in soil: Other adverse effects (such as

hazardous to the ozone layer):

No data available No data available No data available

Ecological Toxicity Data

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

13. Disposal considerations

Description of waste residues: Spent or discarded material may be a hazardous waste. Safe Handling of Waste:

Disposal must be in accordance with applicable Federal,

State/Provincial and Local regulations.

Waste treatment methods (including packaging):

Dispose of by incineration following Federal, State, Local, or

Provincial regulations.

14. Transport information

UN proper shipping name: The DOT Classification for shipping is dependent on quantity,

type of packaging (a kit may include other components), or

method of shipment.

Product Name: Multi-Purpose Epoxy Cartridge

Product identifier: 100818 Revision Date: 07-18-2015

Replaces:

15. Regulatory information

TSCA Status: The intentional ingredients of this product are listed.

Regulated Components:

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Styrene	100-42-5	N	N	Υ	N

16. Other information, including date of preparation or last revision.

Revision Date: 07-18-2015

Revision Number: 4

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances