Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/15/2015

Product form

: Mixture

Trade name

O'REILLY'S CARB & CHOKE CLEANER 12.5 OZ.

Product code

ORC72414

Parament to entract uses a some successive

Use of the substance/mixture

: Carburetor Cleaner

Flagger of the supplied and the Same of the classes O'Reilly Auto Parts 233 South Patterson

Springfield, Missouri 65802 T 417-862-2674

Emergency number

CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

Flam, Aerosol 2 H223 Compressed gas H280 Acute Tox. 3 (Oral) H301 Acute Tox. 3 (Dermal) H311 Skin Irrit. 2 H315 Eye Irrit. 2A H319 Repr. 2 H361 STOT SE 1 H370 STOT SE 3 H336 STOT RE 2 H373

Full text of H-phrases: see section 16

ad Labor elements

Hazard pictograms (GHS-US)



GHS02

GHS04







Version: 1.1

Signal word (GHS-US)

Hazard statements (GHS-US)

Danger

H223 - Flammable aerosol

H280 - Contains gas under pressure; may explode if heated H301+H311 - Toxic if swallowed or in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US)

P201 - Obtain special instructions

P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking

P211 - Do not spray on an open flame or other ignition source P251 - Pressurized container: Do not pierce or burn, even after use

P260 - Do not breathe dust, fumes, gas, mist, vapor spray P261 - Avoid breathing dust, fume, gas, mist, vapor spray P264 - Wash affected areas thoroughly after handling

P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves, protective clothing, eye protection, face protection P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,

P302+P352 - If on skin: Wash with plenty of soap and water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes; Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P307+P311 - If exposed: Call a poison center/doctor

P308+P313 - If exposed or concerned: Get medical advice/attention

P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.

P314 - Get medical advice/attention if you feel unwell

P321 - Specific treatment: See section 4.1 on SDS

P330 - Rinse mouth

P332+P313 - If skin irritation occurs: Get medical advice/attention

P337+P313 - If eye irritation persists: Get medical advice/attention

P361 - Take off immediately all contaminated clothing

P362 - Take off contaminated clothing and wash before reuse

P363 - Wash contaminated clothing before reuse

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P410+P403 - Protect from sunlight. Store in a well-ventilated place

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with

local, regional, national, international regulations.

25 Oher mens

Other hazards not contributing to the classification

Contains gas under pressure; may explode if heated.

24 Union and sexual (CHSUS)

No data available

SECTION 3: Composition/Information on Ingredients

Not applicable

312 Missons

Name	Productidentifler	%	Classification (GHS-US)
Acetone	(CAS No) 67-64-1	30 - 50	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Toluene	(CAS No) 108-88-3	10 - 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Methanol	(CAS No) 67-56-1	10 - 30	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370
Carbon Dioxide, Liquefied, Under Pressure	(CAS No) 124-38-9	5 - 10	Compressed gas, H280

The exact percentage is a trade secret.

SECTION 4; First ald measures

41 Jesannis entret na re

First-aid measures general

Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician.

First-aid measures after inhalation

Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact

Rinse skin with water/shower. Immediately call a poison center or doctor/physician. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Immediately call a poison center or doctor/physician. Obtain medical attention if pain, blinking or redness persist. Direct contact with the eyes is likely to be irritating.

First-aid measures after ingestion

Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a poison center or doctor/physician.

Symptoms/injuries

Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/injuries after inhalation Symptoms/injuries after skin contact

- \$\text{\$\text{\$}}\$ Shortness of breath. May cause drowsiness or dizziness.
- Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.

Symptoms/injuries after eye contact

Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue. Causes serious eye irritation.

Symptoms/injuries after ingestion

Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

18/05/2015

EN (English US)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

No additional information available

SECTION 5: Firefighting manages

Ezitigotak ng madio

Suitable extinguishing media

Unsuitable extinguishing media

Foam, Dry powder, Carbon dioxide, Water spray, Sand.

Do not use a heavy water stream.

Fire hazard

Flammable aerosol.

Explosion hazard

: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

At desta restaurant Firefighting instructions

: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire

reaches explosives. Evacuate area.

Protection during firefighting

Do not enter fire area without proper protective equipment, including respiratory protection.

Other information

: Aerosol Level 2.

SECTION 6; Accidental release measures

General measures

No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

Protective equipment

Gloves. Safety glasses.

Emergency procedures

Evacuate unnecessary personnel.

Protective equipment

: Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.

Emergency procedures

: Ventilate area.

t. I vier contain a comme

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

l'a sonate agrungas e stert va er

Mathematical and afformed all montand elements

For containment

: Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the

leak, cut off the supply.

1600

Methods for cleaning up

: Store away from other materials.

A Resolvent to tend of tellar

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling one storage

Additional hazards when processed

Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions . Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area. Do not breathe

dust,fumes,gas,mist,vapor spray.

Hygiene measures

Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately.

12. Conditions to the started business will be

Technical measures

Comply with applicable regulations. Proper grounding procedures to avoid static electricity

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.

Incompatible products

Incompatible materials

Sources of ignition. Direct sunlight. Heat sources.

Storage area

Store in a well-ventilated place.

Strong bases. Strong acids.

18/05/2015

EN (English US)

3/1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Fig. Summer man goals

Follow Label Directions.

SECTION 8: Expending controls/personal protection

Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (mg/m³)	75 mg/m³
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
Carbon Dioxide, Liqu	efied, Under Pressure (124-38-9)	
USA ACGIH	ACGIH TWA (mg/m³)	9000 mg/m³
USA ACGIH	ACGIH TWA (ppm)	5000 ppm
USA ACGIH	ACGIH STEL (mg/m³)	54000
USA ACGIH	ACGIH STEL (ppm)	30000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	9000 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm
Methanoi (67-56-1)		
USA ACGIH	ACGIH TWA (mg/m³)	262 mg/m³
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (mg/m³)	328 mg/m³
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Benzene (71-43-2)		
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA ACGIH	ACGIH STEL (ppm)	5 ppm
USA ACGIH	ACGIH Ceiling (ppm)	25 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm
Acetone (67-64-1)		
USA ACGIH	ACGIH TWA (mg/m³)	1188 mg/m³
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA ACGIH	ACGIH STEL (mg/m³)	1782 mg/m³
USA ACGIH	ACGIH STEL (ppm)	750 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	2400 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

Appropriate engineering controls
Personal protective equipment

- Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.
- Gloves. Safety glasses. Avoid all unnecessary exposure.





Hand protection

Eye protection

Skin and body protection

Respiratory protection

Other information

- Wear protective gloves.
- Chemical goggles or safety glasses.
- : Wear suitable protective clothing.
- Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
- Do not eat, drink or smoke during use.

18/05/2015

EN (English US)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Physical state : Gas Appearance Liquid.

Color Colourless to light yellow.

Characteristic. Solvent-like odour. Odor

Odor threshold No data available pH No data available Relative evaporation rate (butyl acetate=1) No data available Melting point : No data available

Freezing point -78 °C (Lowest Component-Acetone) 56.11 °C (Lowest Component-Acetone) Boiling point Flash point -18 °C (Lowest Component-Acetone)

No data available Auto-ignition temperature Decomposition temperature No data available Flammability (solid, gas) No data available : No data available Vapor pressure 🥫 No data available Relative vapor density at 20 °C

: 0.82 Relative density Specific gravity / density : 0.82 g/cm3

: Poorly soluble in water. Solubility Log Pow No data available : No data available Log Kow Viscosity, kinematic : No data available : No data available Viscosity, dynamic

Heating may cause a fire. Heating may cause an explosion, Explosive properties

No data available Oxidizing properties **Explosion limits** : No data available

2 2 Oster interior

: 45 % VOC content Gas group Liquefied gas

SECTION 10. Stability and reactivity

No additional information available

102 Che presented my Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3 Promity Characabarrication

Not established.

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

Strong acids. Strong bases.

10 h tree nevelot mermat.

106 Parrienn, torre or the protects

Toxic fume. . Carbon monoxide. Carbon dioxide.

The later a street and province of rather a fraction

Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Acute toxicity

Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87)
LC50 inhalation rat (mg/l)	> 28.1 mg/l/4h (Rat; Air, Literature study)

5/1 18/05/2015 EN (English US)

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)		
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution	
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors	
LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air	
Benzene (71-43-2)		
LD50 oral rat	> 930 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; > 2000 mg/kg bodyweight; Rat; Experimental value)	
LD50 dermal rabbit	> 8240 mg/kg (Rabbit; Experimental value; 21 CFR 191.10; > 9.4; Rabbit)	
LC50 inhalation rat (mg/l)	43.767 mg/l/4h (Rat; Experimental value)	
LC50 inhalation rat (ppm)	13700 ppm/4h (Rat; Experimental value)	
Acetone (67-64-1)		
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)	
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)	
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)	
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)	
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/irritation	Causes serious eye irritation.	
Respiratory or skin sensitization	Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Toluene (108-88-3)		
IARC group	3	
Benzene (71-43-2)		
IARC group	1	
Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
Specific target organ toxicity (single exposure)	Causes damage to organs. May cause drowsiness or dizziness.	
Specific target organ toxicity (repeated exposure)	May cause damage to organs through prolonged or repeated exposure.	
spiration hazard	: Not classified	
Potential Adverse human health effects and symptoms	Based on available data, the classification criteria are not met. Toxic if swallowed. Toxic in contact with skin.	
symptoms/injuries after inhalation	Shortness of breath. May cause drowsiness or dizziness.	
ymptoms/injuries after skin contact	Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.	
ymptoms/injuries after eye contact	Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue Causes serious eye irritation.	
	· · · · · · · · · · · · · · · · · · ·	
ymptoms/injuries after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.	

12.1.	Taxons		
Tolue	ne (108-88-3)		

10100110 (10000)		
LC50 fish 1	24 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)	
EC50 Daphnia 1	84 mg/l (24 h; Daphnia magna; Locomotor effect)	
LC50 fish 2	13 mg/l (96 h; Lepomis macrochirus)	
EC50 Daphnia 2	11.5 - 19.6 mg/l (48 h; Daphnia magna)	
Threshold limit algae 1	> 400 mg/l (168 h; Scenedesmus quadricauda; Toxicity test)	
Threshold limit algae 2	105 mg/l (192 h; Microcystis aeruginosa)	
Carbon Dioxide, Liquefied, Under Pressur	. (124-38-9)	
LC50 fish 1	35 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); Lethal)	
LC50 fish 2	60 - 240 mg/l (12 h; Salmo gairdneri (Oncorhynchus mykiss); Lethal)	
Метьелої (67-56-1)		
LC50 fish 1	15400 mg/l (96 h; Lepomis macrochirus; Lethal)	
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna; Lethal)	
LC50 fish 2	10800 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)	
EC50 Daphnia 2	24500 mg/l (48 h; Daphnia magna; Locomotor effect)	
Threshold limit other aquatic organisms 1	6600 mg/l (16 h; Pseudomonas putida)	
Threshold limit algae 1	530 mg/l (192 h; Microcystis aeruginosa)	

18/05/2015

EN (English US)

Methanol (67-56-1)	
Threshold limit algae 2	8000 mg/l (168 h; Scenedesmus quadricauda)
Benzene (71-43-2)	
LC50 fish 1	5.3 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	18 mg/l (24 h; Daphnia magna)
LC50 fish 2	15.1 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 2	10 mg/l (48 h; Daphnia magna)
TLM fish 1	22.5 mg/l (96 h; Lepomis macrochirus; Soft water)
TLM fish 2	32 mg/l (96 h; Pimephales promelas; Hard water)
Threshold limit algae 1	100 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)
Threshold limit algae 2	50 mg/l (24 h; Phaeodactylum; Photosynthesis)
Acetone (67-64-1)	or man (2 + m, 1 massacos) tamp 1 motos y tampos to y
_C50 fish 1	6210 mg/l (06 h; Dimanhalas promalas; Naminal sancantration)
EC50 Daphnia 1	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)
_C50 fish 2	8800 mg/l (48 h; Daphnia pulex)
TLM fish 1	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
TLM fish 2	13000 ppm (96 h; Gambusia affinis; Turbulent water)
	> 1000 ppm (96 h; Pisces)
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)
Acetone (67-64-1)	
ΓLM fish 1	13000 ppm (96 h; Gambusia affinis; Turbulent water)
ΓLM fish 2	> 1000 ppm (96 h; Pisces)
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)
Processor search and an arrange	
D'REILLY'S CARB & CHOKE CLEANER 12	5.07
Persistence and degradability	Not established.
	Not established.
Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69 % ThOD
Carbon Dioxide, Liquefied, Under Pressure	(124-38-9)
Persistence and degradability	Biodegradability: not applicable. Not applicable (gas).
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ΓhOD	Not applicable
BOD (% of ThOD)	Not applicable
Methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water, Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance
BOD (% of ThOD)	0.8 % ThOD

Readily biodegradable in water. Ozonation in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air.

18/05/2015

ThOD

BOD (% of ThOD) Benzene (71-43-2)

BOD (% of ThOD)

Persistence and degradability

Biochemical oxygen demand (BOD)

Chemical oxygen demand (COD)

0.70 % ThOD

2.18 g O₂ /g substance

2.15 g O₂ /g substance

3.10 g O₂ /g substance

Safety Data Sheet

Acetone (67-64-1)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available. Not established.	
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance	
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance	
ThOD	2.20 g O ₂ /g substance	
BOD (% of ThOD)	(20 day(s)) 0.872	
Acetone (67-64-1)		
Persistence and degradability	Not established.	
27 Bionsol na Weive softent a		
O'REILLY'S CARB & CHOKE CLEANER	12.5.07	
Bioaccumulative potential	Not established.	
Toluene (108-88-3)		
BCF fish 1	13.2 (Anguilla japonica)	
BCF fish 2	90 (72 h; Leuciscus idus)	
BCF other aquatic organisms 1	380 (24 h; Chlorella sp.; Fresh weight)	
BCF other aquatic organisms 1	4.2 (Mytilus edulis; Fresh weight)	
Log Pow	2.73 (Experimental value; Other; 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
CarbbniDioxide, Liqueried, Winder Press		
Log Pow	0.83 (Experimental value)	
Bioaccumulative potential	Bioaccumulation: not applicable.	
Methenol (67-56-1)		
BCF fish 1	< 10 (72 h; Leuciscus idus)	
BCF fish 2	1 (72 h; Cyprinus carpio; Blood)	
Log Pow	-0.77 (Experimental value; Other)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
Benzene (71-43-2)		
BCF fish 1	19 Salmo gairdneri (Oncorhynchus mykiss)	
BCF fish 2	< 10 (3 days; Leuciscus idus)	
BCF other aquatic organisms 1	30 (24 h; Chlorella sp.; Fresh weight)	
Log Pow	2.13 (Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
Acetone (67-64-1)		
BCF fish 1	0.69 (Pisces)	
BCF other aquatic organisms 1	3	
Log Pow	-0.24 (Test data)	
Bioaccumulative potential	Not bioaccumulative. Not established.	
Асеколе (67-\$4-1)		
Bioaccumulative potential	Not established.	
2.4 Mobility in soil		
Toluene (108-88-3)		
Surface tension	0.03 N/m (20 °C)	
Methanol (67-56-1)		
Surface tension	0.023 N/m (20 °C)	
	0.020 (4/11) (20 0)	
Benzone (71-43-2)	0.000 N/m (00.00)	
Surface tension	0.029 N/m (20 °C)	

12:5 Other adve se effects

Acetone (67-64-1) Surface tension

Other information

Avoid release to the environment.

SECTION 13: Disposal consideration

Waste disposal recommendations

Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

18/05/2015

EN (English US)

0.0237 N/m (20 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Additional information

Flammable vapors may accumulate in the container.

Ecology - waste materials

Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14. T.,

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground):

UN1950, Aerosols, 2.1, Limited Quantity

ICAO/IATA (air):

UN1950, Aerosols, 2.1, Limited Quantity

IMO/IMDG (water):

UN1950, Aerosols, 2.1, Limited Quantity

Special Provisions:

N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

Proper Shipping Name (DOT)

Transport hazard class(es) (DOT)

flammable, (each not exceeding 1 L capacity) 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT)

2.1 - Flammable gas



DOT Special Provisions (49 CFR 172,102)

DOT Packaging Exceptions (49 CFR 173.xxx)

DOT Packaging Non Bulk (49 CFR 173.xxx)

DOT Packaging Bulk (49 CFR 173.xxx)

N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

: 306

None None

14.3 Additional information

Emergency Response Guide (ERG) Number

24-HOUR EMERGENCY INFORMATION: CHEMTREC (800) 424-9300

Other information

No supplementary information available.

Class (ADR)

: 2 - Gases

DOT Vessel Stowage Location

∴ A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other

48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

DOT Quantity Limitations Passenger aircraft/rail # 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 👙 150 kg

Tail of Stramour agreement

CFR 175.75)

SECTION 15: Regulatory informatio

O'REILLY'S CARB & CHOKE CLEANER 12.5 OZ.

SARA Section 311/312 Hazard Classes

Delayed (chronic) health hazard

Fire hazard

Immediate (acute) health hazard Sudden release of pressure hazard

Toluene (108-88-3)

Listed on United States SARA Section 313

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on the United States SARA Section 302

SARA Section 311/312 Hazard Classes

Delayed (chronic) health hazard

Fire hazard

Immediate (acute) health hazard

18/05/2015

EN (English US)

9/1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanoi (67-56-1) Listed on United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Listed on the United States SARA Section 355 SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard Benzene (71-43-2) Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313 Acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on United States SARA Section 313

SARA Section 311/312 Hazard Classes

Immediate (acute) health hazard

Fire hazard

Delayed (chronic) health hazard

O'REILLY'S CARB & CHOKE CLE	ANER 12.5 OZ.	
WHMIS Classification	Class B Division 5 - Flammable Aerosol	
Totuene (108-88-3)		
Listed on the Canadian DSL (Domes	etic Sustances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Methanol (67-56-1)		
Listed on the Canadian DSL (Domes	stic Sustances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effect Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Benzene (71-43-2)		
Listed on the Canadian DSL (Domes	etic Sustances List)	

Class B Division 2 - Flammable Liquid

WHMIS Classification

Acetone (67-64-1)

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Toluene (108-88-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Methanoi (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Benzene (71-43-2)

Acetone (67-64-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Canadian DSL (Domestic Sustances List)

Repr.Cat.3; R63

F; R11

T; R39/23/24/25

Xn: R20/21/22

Xn; R48/20

Xi: R36/38

Full text of R-phrases: see section 16

1522 Name of Larry

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanoi (67-56-1)

Listed on the Canadian IDL (Ingredient Disclosure List)

Benzene (71-43-2)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECI (Korean Existing Chemicals Inventory)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

The US Seate required	2.44 a.,				
O'REILLY'S CARB & CI	HOKE CLEANER 12.5 OZ.				
U.S California - Proposition 65 - Carcinogens List		No			
U.S California - Proposition 65 - Developmental Toxicity		No			
U.S California - Propos Toxicity - Female	sition 65 - Reproductive	No			
U.S California - Propos Toxicity - Male	sition 65 - Reproductive	No			
State or local regulations	3	U.S California - Proposition	65 - Maximum Allowable Dose	Levels (MADL)	
Toluene (108-88-3)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk leve (NSRL)	
No	Yes	Yes	No		
Carbon Dioxide, Liquet	fied, Under Pressure (124-38-5	9)	*	-): 	
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)	
No	No	No	No		
Methanol (67-56-1)				·	
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)	
No	Yes	No	No		
Benzene (71-43-2)				_	
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)	
Yes	Yes	No	Yes		
Acetone (67-64-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)	
Yes	No	No	No		
Acotone (67-64-1)				N.	
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk leve (NSRL)	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

 Acetone (67-64-1)
 No
 No
 No

Toluene (108-88-3)

State or local regulations

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

U.S. - New Jersey - Special Health Hazards Substances List

New Jersey Right-to-Know

U.S. - Massachusetts - Right To Know List

Rhode Island Right to Know

U.S. - Michigan - Critical Materials List

U.S. - New Jersey - Environmental Hazardous Substances List

U.S. - Illinois - Toxic Air Contaminants

U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Methanol (67-56-1)

State or local regulations

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

New Jersey Right-to-Know

Florida Right to Know

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) List

Benzene (71-43-2)

State or local regulations

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

U.S. - Pennsylvania - RTK (Right to Know) List

New Jersey Right-to-Know

Acetone (67-64-1)

State or local regulations

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

Benzene 71-43-2

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16; Other Information

Other information

None.

Full text of H-phrases:

t of reprilates.	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 2	Flammable aerosol Category 2
Flam. Liq. 2	Flammable liquids Category 2
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H223	Flammable aerosol
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated exposure

18/05/2015

EN (English US)

12/1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard


2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity

0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Arter de la com-

Health

2 Moderate Hazard - Temporary or minor injury may occur

Flammability

3 Serious Hazard

Physical

1 Slight Hazard

Personal Protection

: B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this MSDS has avaluated this product and cartifies it to be labilist and packaged in compliance with the applicable provisions of this Faderal Hazardous. Substance Act as stated in 16 CFR 1500 and enforced by the Consumar Product Safety Commission, and where applicable the product that require Codd Resistant Closures are packaged in accordance with the Poison Provention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the above. The date of manufacture is stamped on the product.

Discialment: The information and recommendations contained herein are based upon tests believed to be rullable. However, the manufacturer/distributor of this product does not guarantee that accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED. AS TO THE SAFETY OF THE GOODS. THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to contain to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results, obtained or for incidental or consequential damagns including tost profits arising from the use of these data. No warranty against infringement of any patent, copyright or trudemark is made or implied.