# SAFETY DATA SHEET

### 1. Identification


Product number	425
Product identifier	19 OZ PROCLEAN GERMICIDL CLN 425 LB 12PK
Company information	NICHOLS PAPER COMPANY
	1391 JUDSON ROAD
	SPRING LAKE, MI 49456 United States
Company phone	800-442-0213
Emergency telephone US	1-866-836-8855
Version #	01
Recommended use	Cleaner
Recommended restrictions	None known.

#### 2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Skin corrosion/irritation	Category 1
	Serious eye damage/eye irritation	Category 1
OSHA defined hazards	Not classified.	

### **OSHA** defined hazards

Label elements



#### Supplemental information

Not applicable.

#### 3. Composition/information on ingredients

**Mixtures** 

Chemical name	Common name and synonyms	CAS number	%
2-Butoxyethanol		111-76-2	2.5 - 10
Butane		106-97-8	1 - 2.5
EDTA Tertrasodium Salt		64-02-8	1 - 2.5
Other components below reportable lev	vels		90 - 100

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician or poison control center immediately.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Chemical burns must be treated by a physician. Call a physician or poison control center immediately. For minor skin contact, avoid spreading material on unaffected skin.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Corrosive effects. May cause temporary blindness and severe eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

Suitable extinguishing media	Water.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the MSDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the MSDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure. Do not get this material on clothing. Use only in well-ventilated areas. Observe good industrial hygiene practices. Wash hands thoroughly after handling.
Conditions for safe storage, including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the MSDS). Level 1 Aerosol (NFPA 30B)

### 8. Exposure controls/personal protection

#### **Occupational exposure limits**

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Value Type PEL 2-Butoxyethanol (CAS 240 mg/m3 111-76-2) 50 ppm **US. ACGIH Threshold Limit Values** Components Type Value 2-Butoxyethanol (CAS TWA 20 ppm 111-76-2) US. NIOSH: Pocket Guide to Chemical Hazards Components Value Type 2-Butoxyethanol (CAS TWA 24 mg/m3 111-76-2) 5 ppm Butane (CAS 106-97-8) TWA 1900 mg/m3 800 ppm **Biological limit values ACGIH Biological Exposure Indices** Determinant Specimen Components Value Sampling Time 2-Butoxyethanol (CAS 200 mg/g Butoxyacetic Creatinine in 111-76-2) acid (BAA), urine with hydrolysis \* - For sampling details, please see the source document. **Exposure guidelines** US - California OELs: Skin designation 2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin. US - Minnesota Haz Subs: Skin designation applies 2-Butoxyethanol (CAS 111-76-2) Skin designation applies. US - Tennesse OELs: Skin designation 2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin. US NIOSH Pocket Guide to Chemical Hazards: Skin designation 2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin. US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Can be absorbed through the skin. 2-Butoxyethanol (CAS 111-76-2) Appropriate engineering Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates controls should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Individual protection measures, such as personal protective equipment Eye/face protection Wear eye/face protection. Wear safety glasses with side shields (or goggles). Hand protection Wear protective gloves. Other Wear appropriate chemical resistant clothing. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an **Respiratory protection** air-supplied respirator. Thermal hazards Wear appropriate thermal protective clothing, when necessary. **General hygiene** When using, do not eat, drink or smoke. Do not get this material on clothing. Always observe good considerations personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. 9. Physical and chemical properties

Appearance	Liquid.
Color	Not available.
Form	Aerosol.
Physical state	Gas.
Flash point	-156.00 °F (-104.44 °C) Propellant estimated

Melting point/freezing point	Not available.
Odor	Not available.
pH value	Not available.
Solubility(ies)	Not available.
Vapor density	Not available.
Vapor pressure	55 - 75 psig @70F estimated
Viscosity	Not available.
Other information	
Specific gravity	0.979 estimated

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. This product may react with oxidizing agents. Do not mix with other chemicals.
Hazardous decomposition products	No hazardous decomposition products are known.

### 11. Toxicological information

#### Information on likely routes of exposure

Ingestion	Causes digestive tract burns.	
Inhalation	Prolonged inhalation may be harmful. May cause irritation to the respiratory system.	
Skin contact	Causes severe skin burns.	
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.	
Eye contact	Causes severe eye burns. Causes serious eye damage.	
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.	

#### Information on toxicological effects

#### Acute toxicity

Product	Species	Test Results
19 OZ PROCLEAN GERMI	ICIDL CLN 425 LB 12PK (CAS Mixture)	
Acute		
Dermal		
LD50	Rabbit	4579.8975 mg/kg, estimated
Inhalation		
LC50	Cat	1308.772 mg/l, If <1L: Consumer Commodity Hours, estimated
	Mouse	32265.7188 mg/l, 2 Hours, estimated
		14578.7773 mg/l, 7 Hours, estimated
		12464.9121 mg/l, 10 Minutes, estimated
		5894.7368 mg/l, If <1L: Consumer Commodity Hours, estimated
	Rabbit	12368.4209 mg/l, If <1L: Consumer Commodity Hours, estimated
	Rat	13333.334 mg/l, 2 Hours, estimated
		8947.3682 mg/l, If <1L: Consumer Commodity Hours, estimated
		7208.3047 mg/l, 4 Hours, estimated
		44.7715 mg/l/4h, estimated

Product	Species	Test Results
LCL0	Cat	8596.4912 mg/l, If <1L: Consumer Commodity Hours, estimated
	Rabbit	8596.4912 mg/l, If <1L: Consumer Commodity Hours, estimated
	Rat	2456.1404 mg/l, If <1L: Consumer Commodity Hours, estimated
Oral		
LD50	Guinea pig	24.9502 g/kg, estimated
	Mouse	24.9357 g/kg, estimated
	Rabbit	6.6646 g/kg, estimated
0.11	Rat	9277.7227 mg/kg, estimated
Other LD50	Dog	7934.4087 g/kg, estimated
ED30	Mouse	11678.998 mg/kg, estimated
	Rabbit	5831.5107 mg/kg, estimated
	Rat	6863.7383 mg/kg, estimated
Components	Species	Test Results
2-Butoxyethanol (CAS 111-76-2)	-	Test Nesults
Acute		
Dermal		
LD50	Rabbit	220 mg/kg
Inhalation		
LC50	Mouse	700 mg/l, 7 Hours
	Rat	450 mg/l, 4 Hours
		2.21 mg/l/4h
Oral		
LD50	Guinea pig	1.2 g/kg
	Mouse	1.2 g/kg
	Rabbit	0.32 g/kg
	Rat	470 mg/kg
Other LD50	Mouse	1130 mg/kg
LD30	Rabbit	280 mg/kg
	Rat	340 mg/kg
Butane (CAS 106-97-8)	Nat	540 mg/kg
Acute		
Inhalation		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
EDTA Tertrasodium Salt (CAS 64	4-02-8)	
Acute		
Oral	Det	5 0000 m m/lum
LD50	Rat	> 2000 mg/kg
<i>Other</i> LD50	Mouse	330 mg/kg
	Rat	4000 mg/kg
	, var	
* Estimates for product may	be based on additional component data not shown.	
Skin corrosion/irritation	Causes severe skin burns and eye damage.	
Serious eye damage/eye irritation	Causes severe eye burns. Causes serious eye dam	age.
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause skin sensitiza	tion.

Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall	Evaluation of Carcinogenicity	
2-Butoxyethanol (CAS 11	1-76-2) 3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not likely, due to the form of the product.	
Chronic effects	Prolonged inhalation may be harmful. May be harmful if absorbed through skin.	
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.	

### 12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the<br/>possibility that large or frequent spills can have a harmful or damaging effect on the environment.ProductSpeciesTest Results

		-	
19 OZ PROCLEAN G	ERMICIDL CLN 42	5 LB 12PK (CAS Mixture)	
Algae	IC50	Algae	86.2182 mg/L, 72 Hours, estimated
Crustacea	EC50	Daphnia	17811.9492 mg/L, 48 Hours, estimated
Fish	LC50	Fish	1165.0076 mg/L, 96 Hours, estimated
Components		Species	Test Results
2-Butoxyethanol (CAS	5 111-76-2)		
Crustacea	EC50	Daphnia	1819 mg/L, 48 Hours
Aquatic			
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
EDTA Tertrasodium S	alt (CAS 64-02-8)		
Algae	IC50	Algae	1.01 mg/L, 72 Hours
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	472 - 500 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential	No data available.
Partition coefficient n-octan	ol / water (log Kow)
2-Butoxyethanol	

Butane2.89Mobility in soilNo data available.Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation<br/>potential, endocrine disruption, global warming potential) are expected from this component.

0.83

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.

#### 14. Transport information


#### DOT

UN number	UN1950
UN proper shipping name	Aerosols, non-flammable
Transport hazard class(es)	2.2
Subsidiary class(es)	Not available.
Packing group	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Labels required	2.2
Packaging exceptions	LTD OTY
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### ΙΑΤΑ

	~	
	UN number	UN1950
	UN proper shipping name	Aerosols, non-flammable, containing substances in Class 8, Packing Group III
	Transport hazard class(es)	2.2
	Subsidiary class(es)	8
	Packaging group	Not available.
	Environmental hazards	No
	Labels required	Not available.
	ERG Code	2C
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IME	DG	
	UN number	UN1950
	UN proper shipping name	AEROSOLS
	Transport hazard class(es)	2.2
	Subsidiary class(es)	8
	Packaging group	Not available.
	Environmental hazards	
	Marine pollutant	No
	Labels required	None
	EmS	Not available.
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	Packaging Exceptions	LTD QTY
Tra	nsport in bulk according to	Not applicable.
An	nex II of MARPOL 73/78 and	
the	IBC Code	
DO	т	



### 15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazar Standard, 29 CFR 1910.1200.	rd Communication	
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)			
Not regulated.			
	CERCLA Hazardous Substance List (40 CFR 302.4)		
Not listed.	ulated Substances (29 CFR 1910.1001-1050)		
Not listed.	ulated Substances (29 CFR 1910.1001-1050)		
SARA 304 Emergency relea	use notification		
Not regulated.			
Superfund Amendments and Re	eauthorization Act of 1986 (SARA)		
Hazard categories	Immediate Hazard - Yes		
	Delayed Hazard - Yes		
	Fire Hazard - Yes Pressure Hazard - Yes		
	Reactivity Hazard - No		
SARA 302 Extremely	No		
hazardous substance			
SARA 311/312 Hazardous chemical	No		
Other federal regulations			
Clean Air Act (CAA) Section	n 112 Hazardous Air Pollutants (HAPs) List		
Not regulated.			
	n 112(r) Accidental Release Prevention (40 CFR 68.130)		
Butane (CAS 106-97-8)			
Safe Drinking Water Act (SDWA)	Not regulated.		
Chemical Code Numbe	ninistration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and r	d 1310.04(f)(2) and	
Not listed.			
Food and Drug Administration (FDA)	Not regulated.		
US state regulations			
US. New Jersey Worker and	d Community Right-to-Know Act		
Butane (CAS 106-97-8)	500 lbs		
US. Pennsylvania RTK - Ha			
2-Butoxyethanol (CAS 1 Butane (CAS 106-97-8)	11-76-2)		
US. California Proposition	65		
	Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is a carcinogens or reproductive toxins.	is not known to contain any	
International Inventories			
Country(s) or region	Inventory name	On inventory (yes/no)*	
Australia	Australian Inventory of Chemical Substances (AICS)	No	
Canada	Domestic Substances List (DSL)	Yes	
Canada	Non-Domestic Substances List (NDSL)	No	
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes	
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No	
Europe	European List of Notified Chemical Substances (ELINCS)	No	
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes	
Korea	Existing Chemicals List (ECL)	No	
New Zealand	New Zealand Inventory	No	
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No	

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes \*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

,	<b>5 1 1</b>
Issue date	05-15-2014
Version #	01
Further information	Not available.
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Product and Company Identification: Product and Company Identification GHS: Classification